

Пропускная способность галл/мин. @40 фунт/дюйм кв.	Размер трубопровода соединения	Номер в каталоге		Ø сопла	Пропускная способность галлонов в минуту (давление в фунтах на дюйм квадратный)													Углы распыления (также в фунтах на дюйм кв.)			
					3	5	7	10	15	20	30	40	60	80	100	ISO	7	20	40	SO	
.80	1/8	SFQ81	SMQ81	.062	.22	.28	.33	.40	.49	.57	.71	.80	.96	1.1	1.3	1.6	55°	60°	60°	60°	
1.0	1/8	SFQ101	SMQ101	.062	.27	.35	.42	.50	.61	.71	.87	1.0	1.2	1.4	1.6	1.9	60°	70°	70°	70°*	
1.2	1/8	SfQ121	SMO121	.062	.34	.42	.50	.60	.74	.84	1.0	1.2	1.4	1.6	1.8	2.3	65°	75°	75°	75°	
1.6	1/4	SK3162	SMQ162	.086	.44	.57	.67	.80	.98	1.1	1.4	1.6	2.0	2.3	2.5	3.1	55°	60°	60°	60°	
2.0	1/4	SF«202	SMQ202	.086	.55	.71	.84	1.0	1.2	1.4	1.7	2.0	2.4	2.8	3.2	3.9	65°	70°	70°	70°	
2.4	1/4	SFQ242	SMQ242	.086	.68	.85	1.0	1.2	1.5	1.7	2.1	2.4	2.8	3.3	3.7	4.6	70°	75°	75°	75°	
3.0	3/8	SFQ303	SMGJ03	.098	.82	1.1	1.3	1.5	1.8	2.1	2.6	3.0	3.7	4.2	4.7	5.8	75°	80°	80°	80°	
3.6	3/8	SFQ363,	SMQ363	.098	.99	1.3	1.5	1.8	2.2	2.5	3.1	3.6	4.3	5.0	5.6	6.9	75°	80°	SO-	80°	
4.0	3/8	SFCH03	SMQ403	.098	1.1	1.4	1.7	2.0	2.4	2.8	3.5	4.0	4.9	5.6	6.3	7.8	75°	80°	SO0	80°	
5.0	1/2	SKJ504	SMQ504	.142	1.4	1.8	2.1	2.4	3.0	3.5	4.3	5.0	6.1	7.1	7.9	9.7	65°	70°	70°	70°	
5.8	1/2	SFQ584	SMQ584	.142	1.5	2.0	2.4	2.9	3.6	4.1	5.0	5.8	7.1	8.2	9.2	11.2	70°	75°	75°	75°	
6.0	1/2	SFQ604	SMQ604	.142	1.6	2.1	2.5	3.0	3.7	4.2	5.2	6.0	7.3	8.4	9.4	11.6	70°	75°	75°	75°	
7.0	1/2	SFQ704	SMQ704	.142	1.9	2.5	2.9	3.5	4.3	4.9	6.1	7.0	8.6	9.9	11.1	13.6	75°	80°	80°	80°	
7.2	1/2	SfQ724	SMQ724	.142	2.0	2.6	3.0	3.6	4.4	5.1	6.2	7.2	8.7	10.1	11.3	13.9	80°	80°	80°	80°	
.80	1/8		SSMG81	.062	.22	.28	.33	.40	.49	.57	.71	.80	.96	1.1	1.3	1.6	55°	60°	60°	60°	
1.0	1/8			.062				.50	.61	.71	.87	1.0	1.2	1.4	1.6	1.9	"				
1.2	1/8		SSMQ1	.062	.2	.3	.4	.60	.74	.84	1.0	1.2	1.4	1.6	1.8	2.3	60°	70°	70°	70°	

			01		7	5	2										°	°	°	°
			SSMQ1 21		.3 4	.4 2	.5 0										65 °	75 °	75 °	75 °
1.6	1/4		SSMQ1 62	.086	.4 4	.5 7	.6 7	.80	.98	1.1	1.4	1.6	2.0	2.3	2.5	3.1	55 °	60 °	60 °	60 °
2.0	1/4		SSMQ2 02	.086	.5 5	.7 1	.8 4	1.0	1.2	1.4	1.7	2.0	2.4	2.8	3.2	3.9	65 °	70 °	70 °	70 °
2.4	1/4		SSMQ2 42	.086	.6 8	.8 5	1. 0	1.2	1.5	1.7	2.1	2.4	2.8	3.3	3.7	4.6	70 °	75 °	75 °	75 °
3.0	3/8		SSMQ3 03	.098	.8 2	1. 1	1. 3	1.5	1.8	2.1	2.6	3.0	3.7	4.2	4.7	5.8	75 °	80 °	80 °	80 °
3.6	3/8		SSMQ3 63	.098	.9 9	1. 3	1. 5	1.8	2.2	2.5	3.1	3.6	4.3	5.0	5.6	6.9	75 °	80 °	80 °	80 °
4.0	3/8		SSMQ4 03	.098	1. 1	1. 4	1. 7	2.0	2.4	2.8	3.5	4.0	4.9	5.6	6.3	7.8	75 °	80 °	80 °	80 °
5.0	1/2		SSMQ6 04	.142	1. 4	1. 8	2. 1	2.4	3.0	3.5	4.3	5.0	6.1	7.1	7.9	9.7	65 °	70 °	70 °	70 °
5.8	1/2		SSMQ5 84		1. 5	2. 0	2. 4							8.2	9.2	11. 2	70 °	75 °	75 °	75 °
6.0	1/2		SSMQ6 04	.142	1. 6	2. 1	2. 5	2.9	3.6	4.1	5.0	5.8	7.1	8.4	9.4	11. 6	70 °	75 °	75 °	75 °
7.0	1/2		SSMQ7 04	.142	1. 9	2. 5	2. 9	3.5	4.3	4.9	6.1	7.0	8.6	9.9	11. 1	13. 6	75 °	80 °	80 °	so -
7.2	1/2		SSMQ7 24	.142	2. 0	2. 6	3. 0	3.6	4.4	5.1	6.2	7.2	8.7	10. 1	11. 3	13. 9	80 °	80 °	80 °	so 0
8.0	1/2		SSMQ8 04	.142	2. 2	2. 8	3. 3	4.0	4.9	5.7	6.9	8.0	9.8	11. 2	12. 7	15. 5	80 °	80 °	80 °	75 °
10.0	3/4		SSMQ1 006	.190	2. 7	3. 6	4. 2	4.9	6.1	7.1	8.7	10. 0	12. 3	14. 2	15. 8	19. 4	70 °	75 °	75 °	75 °
12.0	3/4		SSMQ1 206	.190	3. 3	4. 3	5. 0	6.0	7.3	8.5	10. 4	12. 0	14. 7	17. 0	19. 0	23. 2	75 °	80 °	80 °	80 °
16.0	3/4		SSMQ1 606	.190	4. 4	5. 7	6. 7	8.0	9.8	11. 3	13. 8	16. 0	19. 6	22. 6	25. 3	31. 0	85 °	90 °	90 °	90 °
20.0	1		SSMQ2 008	.244	5. 5	7. 1	8. 4	10. 0	12. 2	14. 1	17. 3	20. 0	24. 5	28. 2	31. 6	38. 8	75 °	80 °	80 °	80 °

www.vitaprom.ru

www.satronic.ru