

Пропускная способность галл/мин. @40 фунт/дюйм кв.	Размер трубного соединения	Номер в каталоге		Диаметр сопла	Пропускная способность галлонов в минуту (давление в фунтах на дюйм квадратный)											Углы распыления (также в фунтах на дюйм кв.)		
		«мама»	«папа»		5	7	10	15	20	30	40	60	80	100	125	20	40	80
.50	1/4	TSF52	TSM52	.045					.36	.43	.50	.60	.70	.80	.85	40°	45°	45°
.60	1/4	TSF62	TSM62	.045	.21	.25	.30	.37	.42	.52	.60	.73	.85	.95	1.0	52°	55°	55°
80	1/4	TSF82	TSM82	.045	28	33	40	49	57	71	80	96	111	131	144	62°	65°	65°
1.0	1/4	TSF102	TSM102	.045	.35	.42	.50	.61	.70	.86	1.0	1.2	1.4	1.6	1.7	77°	80°	80°
1.5	1/4	TSF152	TSM152	.051	.53	.63	.75	.92	1.1	1.3	1.5	1.8	2.1	2.4	2.7	72°	75°	75°
2.0	1/4	TSF202	TSM202	.051	.71	.84	1.0	1.2	1.4	1.7	2.0	2.5	2.8	3.2	3.5	77°	80°	80°
2.5	3/8	TSF253	TSM253	.064	.91	1.1	1.2	1.5	1.8	2.2	2.5	3.1	3.5	3.9	4.4	62°	65°	65°
3.0	3/8	TSF303	TSM303	.064	1.11	1.35	1.58	2.0	2.4	2.9	3.0	3.7	4.2	4.7	5.2	68°	70°	70°
4.0	3/8	TSF353	TSM353	.064	1.33	1.57	1.81	2.4	2.9	3.5	3.5	4.3	4.9	5.6	6.2	77°	80°	80°
		TSF403	TSM403	.064	1.44	1.70	2.0	2.6	3.2	3.8	4.0	4.9	5.6	6.3	7.2	82°	85°	85°
4.5	3/8	TSF453	TSM453	.075	1.66	1.99	2.28	3.0	3.6	4.3	4.5	5.4	6.3	7.1	7.9	82°	85°	85°
5.0	3/8	TSF503	TSM503	.075	1.88	2.21	2.51	3.3	3.9	4.6	5.0	6.1	7.1	7.9	8.8	82°	85°	85°
3.0	1/2	TSF504	TSM504	.091	1.88	2.21	2.51	3.3	3.9	4.6	5.0	6.1	7.1	7.9	8.8	72°	75°	75°
6.0	1/2	TSF604	TSM604	.091	2.11	2.5	3.0	3.7	4.4	5.2	6.0	7.3	8.5	9.5	10.5	77°	80°	80°
7.0	1/2	TSF704	TSM704	.091	2.5	2.9	3.5	4.3	4.9	5.8	7.0	8.6	9.9	11.1	12.4	77°	80°	80°
8.0	1/2	TSF804	TSM804	.102	2.8	3.3	4.0	4.9	5.6	6.6	8.0	9.8	11.3	12.6	14.2	77°	80°	82°
9.0	1/2	TSF904	TSM904	.102	3.2	3.8	4.5	5.6	6.3	7.5	9.0	11.0	12.6	14.1	15.8	77°	80°	82°
10.0	1/2	TSF1004	TSM1004	.114	3.5	4.2	4.9	6.1	7.0	8.3	10.0	12.0	14.0	15.8	17.6	82°	85°	87°

www.vitaprom.ru

www.satronic.ru

